

## 206 型机械密封

多弹簧双端面平衡型机械密封

Multi-spring Dual-end Balanced Mechanical Seal

适用范围:

SCOPE OF APPLICATION:

压力:0.6-1.6Mpa

pressure:0.6-1.6Mpa

温度:-40+180°C

temperature:-40+180°C

轴径:30-110mm

shaft D:30-110mm

转速:≤500rpm

rotational speed:≤500rpm

注:当温度超过180°C时设置冷却水箱

Note:Install the chilling water tank when it is >180°C.



符号Symbol	d	d <sub>1</sub>	d <sub>2</sub>	D <sub>1</sub>	D <sub>2</sub>	D <sub>3</sub>	D	H	n-φA	重量(公斤)	
公差Tolerance	H <sub>7</sub> /h <sub>8</sub>	h <sub>7</sub>	H <sub>7</sub> /h <sub>8</sub>		h <sub>11</sub>	J <sub>7</sub>				Weight	
轴径 shaft D	30	30	40	45	150	116	85	185	295	4-φ18	20.85
	40	40	50	55	170	135	100	225	297		28.65
	50	50	60	65	200	164	120	235	308		34.49
	65	65	75	80	200	164	140	235	311	8-φ18	37.52
	80	80	90	95	225	188	180	260	339		52.26
	95	95	105	110	255	220	200	290	359		71.81
	110	110	125	130	280	245	230	315	368		91.95